



衬衫缝后复司机

MB3008A-JK-MO-6716S-DE4-40H

SHIRT BACK YOKE SEWING MACHINE

机器型号

Machine model

MB3008A-JK-MO-6716S-DE4-40H

机头配置

Sewing head model

JUKI

最快缝制速度/rpm

Maximum sewing speed

7000

机针型号

Needle type

DCx27

缝制针距长度/mm

stitch length

1.5-4

褶间距/mm

pleat distance range

10-200

中间褶宽/mm

Width of the middle pleat

30-40

两边褶宽/mm

Width of the side pleats

10-20

褶的位置/mm

The position of the pleats

220-240,0.5,1.8

大缝料长度/mm

Length of sewing placket

1800×1550×1600

最大压脚压力/N

Maximum foot pressure

477/602

铁杆行程/mm

Pin rod stroke

24.5

设备尺寸/mm (L*W*H)

Device dimensions

2400*1100*1400

- 1 缝制长度范围大，面料最长可达600mm,满足大部分需求；
 - 2 可通过开关根据面料来进行运行速度的切换、选择，共分为高、中、低三档；
 - 3 左右同步移动的机构，可在自动折叠的中心褶、两边褶、无褶三种类型之间切换，无需任何工具，方便快捷；
 - 4 集自动折叠、自动缝制、自动剪切、自动集灰和自动收料，全程无需人工参与；
 - 5 具有粘合嵌条自动输送装置，无张力嵌条输送机构确保缝制品达到完美效果；
 - 6 自动断线检测功能，确保设备安全运行。
- 1 The sewing length range is wide, with the fabric length reaching up to 600mm, meeting most requirements.
 - 2 The running speed can be switched and selected according to the fabric by using the switch, and it is divided into three levels: high, medium and low.
 - 3 The left and right synchronous moving mechanism can switch between three types of patterns: automatic folding center pleats, both sides pleats and no pleats, without any tools, which is convenient and fast.
 - 4 It integrates automatic folding, automatic sewing, automatic cutting, automatic dust collection and automatic material collection, and no manual participation is required throughout the process.
 - 5 It has an automatic adhesive strip conveying device, and the tension-free adhesive strip conveying mechanism ensures that the sewn products achieve perfect results;
 - 6 The automatic thread break detection function ensures the safe operation of the equipment.

常州智谷机电科技有限公司
IMB AUTOMATION CO.,LTD.

江苏省常州市天宁区华云路33号
NO.33 Huayun Road, Tianning district
changzhou, Jiangsu Province

0519-88856388

sale@imb-china.com

www.imb-china.com

